

# BETTY

**portable self-priming pumps**  
(for garden use)



**BETTY 60**

## **PERFORMANCE RANGE**

Flow rate up to 50 l/min (3 m<sup>3</sup>/h)  
Dynamic head up to 50 m

## **OPERATING LIMITS**

Suction lift up to 9 m  
Fluid temperature up to + 40°C  
Maximum ambient temperature + 40°C

## **CONSTRUCTION AND SAFETY STANDARDS:**

EN 60 335-1  
IEC 335-1  
CEI 61-150

EN 60034-1  
IEC 34-1  
CEI 2-3

## **PUMP INSTALLATION AND APPLICATIONS**

Portable self-priming pumps able to expell air bubbles present in suction pipe.

**THESE PUMPS ARE RECOMMENDED FOR VARIOUS USES, SUCH AS: GARDENING, HORTICULTURE, WASHING, HOBBY APPLICATIONS AND ARE SUITABLE FOR HANDLING LIQUIDS WHICH ARE COMPATIBLE WITH THE COMPONENT PARTS OF THE PUMP.**

## **WARRANTY: 2 YEARS**

(according to our general sales conditions).





**BETTY 2**



**BETTINOX 2**

**PERFORMANCE DATA AT n= 2900 1/min**

PUMP MODEL	POWER		PERFORMANCE		CONNECTIONS	
	Single phase	kW	HP	Q (l/min)	H (meters c.a.)	Suction
BETTY 60	0.37	0.50	5 ÷ 40	38 ÷ 5	1"	1"
BETTY 65	0.50	0.70	5 ÷ 50	50 ÷ 8	1"	1"
BETTY 1	0.37	0.50	5 ÷ 50	32 ÷ 13	1"	1"
BETTY 2	0.50	0.70	5 ÷ 50	36 ÷ 15	1"	1"
BETTY 3	0.60	0.85	5 ÷ 50	42 ÷ 19	1"	1"
BETTINOX 1	0.37	0.50	5 ÷ 50	32 ÷ 13	1"	1"
BETTINOX 2	0.50	0.70	5 ÷ 50	36 ÷ 15	1"	1"
BETTINOX 3	0.60	0.85	5 ÷ 50	42 ÷ 19	1"	1"

**Q = FLOW RATE H = TOTAL DYNAMIC HEAD IN METERS**

Curve tolerance according to ISO 2548.