

GS SERIES

SUBMERSIBLE PUMPS FOR 4" WELLS

APPLICATIONS

- Water supply.
- Sprinkler systems.
- Pressure boosting.
- Fire-fighting.
- Water display, fountains.

SPECIFICATIONS

- **Delivery** up to **21 m³/h.**
- **Head** up to **340 m.**
- **Maximum** pump overall **diameter** (cable cover included): **99 mm.**
- **Maximum** immersion **depth: 150 m.**
- Maximum permissible **quantity of suspended sand: 150 g/m³.**
- 1GSL - 2GS - 4GS - 6GS versions (radial impellers): 1¼" delivery port.
- 8GS - 12GS - 16GS versions (semi-axial impellers): 2" delivery port.
- Rated motor **power** from **0.25 to 7.5 kW.**
- Versions:
 - Single-phase** 220-230 V or 230-240 V, 50 Hz, from 0.25 to 2.2 kW.
 - Three-phase** 380-415 V, 50 Hz, from 0.37 to 7.5 kW.- Overload protection to be provided by user and installed in the control box (see control box section).- Maximum supply voltage variations: +6%/-10%
- Maximum number of **starts per hour**, at regular intervals: **30** (4OS motor), **20** (F4 motor).
- Horizontal operation up to 2.2 kW with 4OS or F4 series motors, with F4 motor for higher powers.
- Maximum **temperature** of water in contact with the motor: **30°C.**

CONSTRUCTION CHARACTERISTICS

PUMP

- Abrasion resistant construction. The front wear plate, combined with the floating impellers, ensures optimum resistance to abrasion.
- The non-return valve is integrated in the head so as to discharge the weight of the column of water and any



water hammer onto the head itself, thus safeguarding impellers and diffusers.

- The upper and lower supports are made of precision-cast stainless steel, ensuring resistance to corrosion, durability and a sturdy coupling to the motor.
- The GS series pumps can be coupled to either 4OS or F4 motors.

MOTOR

For 4OS motor characteristics, please see specific section in this catalogue.

TABLE OF MATERIALS

PART	MATERIAL
Upper head, Valve cap, Valve seat	STAINLESS STEEL (AISI 303 - DIN 1.4305)
Valve gasket	NITRILE RUBBER
Valve stop ring	STAINLESS STEEL (AISI 302 - DIN 1.4319)
Upper support	POLYCARBONATE/FIBERGLASS
Bearing	POLYURETHANE
Diffuser, impeller	POLYCARBONATE/FIBERGLASS
Diffuser case, Shim, Pump shaft, Outer sleeve, Spacer, Filter, Coupling, Cable cover	STAINLESS STEEL (AISI 304 - DIN 1.4301)

All the nitrile rubber, polyurethane and polycarbonate components are suitable for usage with foodstuffs and comply with FDA specification (the Food and Drug Administration is the US agency for the safeguard of public health).

1GSL, 2GS, 4GS, 6GS SERIES

HYDRAULIC PERFORMANCE TABLE AT 2850 rpm, 50 Hz

PUMP TYPE	NUMBER OF STAGES	KW	HP	Q = DELIVERY																RATED CURRENT		CAPACITOR	ELECTRIC PUMP LENGTH	ELECTRIC PUMP WEIGHT
				H = TOTAL HEAD METERS COLUMN OF WATER																SINGLE-PHASE 220 V	THREE-PHASE 380-415 V			
				l/min	0	5	10	15	20	25	30	40	50	60	80	90	110	133	mm					
					0,3	0,6	0,9	1,2	1,5	1,8	2,4	3	3,6	4,8	5,4	6,6	8			450 V				
					m ³ /h																			
1GSL02M	8	0,25	0,33	53	50	44	53	65	26,5									2,5	-	12,5	632	11,5		
1GSL03M	12	0,37	0,5	79	75	66	55	55	40									3,5	-	16	722	13		
1GSL03T	12	0,37	0,5	79	75	66	55	55	40									-	1,1	-	701	12		
1GSL05M	18	0,55	0,75	119	112	100	83	60										4,5	-	20	854	15,5		
1GSL05T	18	0,55	0,75	119	112	100	83	60										-	1,6	-	826	14		
1GSL07M	24	0,75	1	159	150	133	110	80										5,7	-	30	981	17,5		
1GSL07T	24	0,75	1	159	150	133	110	80										-	2,1	-	959	16		
1GSL11M	35	1,1	1,5	232	218	194	160	116										8,2	-	40	1232	21		
1GSL11T	35	1,1	1,5	232	218	194	160	116										-	3	-	1203	20		
1GSL15M	49	1,5	2	324	305	272	224	163										10,5	-	50	1504	25		
1GSL15T	49	1,5	2	324	305	272	224	163										-	4	-	1476	23		
2GS02M	5	0,25	0,33	33						30	28	26	20	13				2,5	-	12,5	579	11		
2GS03M	7	0,37	0,5	47						42	40	36	29	19				3,5	-	16	634	12,5		
2GS03T	7	0,37	0,5	47						42	40	36	29	19				-	1,1	-	614	11		
2GS05M	10	0,55	0,75	67						60	56	52	41	27				4,5	-	20	714	14,5		
2GS05T	10	0,55	0,75	67						60	56	52	41	27				-	1,6	-	686	12,5		
2GS07M	14	0,75	1	93						83	79	73	57	37				5,7	-	30	806	16		
2GS07T	14	0,75	1	93						83	79	73	57	37				-	2,1	-	784	14,5		
2GS11M	20	1,1	1,5	133						119	113	104	82	53				8,2	-	40	940	18		
2GS11T	20	1,1	1,5	133						119	113	104	82	53				-	3	-	911	17		
2GS15M	28	1,5	2	187						167	158	146	115	74				10,5	-	50	1138	21		
2GS15T	28	1,5	2	187						167	158	146	115	74				-	4	-	1110	20		
2GS22M	40	2,2	3	267						238	226	208	164	106				15,9	-	70	1452	28		
2GS22T	40	2,2	3	267						238	226	208	164	106				-	5,9	-	1347	23		
2GS30T	52	3	4	347						309	294	271	213	138				-	7,8	-	1623	31		
4GS03M	4	0,37	0,5	27						24	23	21	19	13				3,5	-	16	598	12		
4GS03T	4	0,37	0,5	27						24	23	21	19	13				-	1,1	-	578	10,5		
4GS05M	7	0,55	0,75	47						42	40	37	33	22	15				4,5	-	20	691	14	
4GS05T	7	0,55	0,75	47						42	40	37	33	22	15				-	1,6	-	663	12	
4GS07M	9	0,75	1	60						54	51	47	42	28	19				5,7	-	30	756	15,5	
4GS07T	9	0,75	1	60						54	51	47	42	28	19				-	2,1	-	734	14	
4GS11M	14	1,1	1,5	94						84	80	74	66	44	30				8,2	-	40	893	17,5	
4GS11T	14	1,1	1,5	94						84	80	74	66	44	30				-	3	-	864	16	
4GS15M	19	1,5	2	127						114	108	100	89	60	40				10,5	-	50	1029	20	
4GS15T	19	1,5	2	127						114	108	100	89	60	40				-	4	-	1001	18,5	
4GS22M	27	2,2	3	181						162	154	142	127	85	57				15,9	-	70	1336	26	
4GS22T	27	2,2	3	181						162	154	142	127	85	57				-	5,9	-	1231	22	
4GS30T	35	3	4	228						204	194	179	160	107	72				-	7,8	-	1471	29	
4GS40T	48	4	5,5	322						288	274	252	226	151	102				-	10	-	2065	35	
6GS05M	5	0,55	0,75	30						26	25	22	21	17	12				4,5	-	20	710	14,5	
6GS05T	5	0,55	0,75	30						26	25	22	21	17	12				-	1,6	-	682	12,5	
6GS07M	7	0,75	1	43						36	35	31	29	24	16				5,7	-	30	794	16	
6GS07T	7	0,75	1	43						36	35	31	29	24	16				-	2,1	-	772	14,5	
6GS11M	10	1,1	1,5	61						52	49	44	41	34	23				8,2	-	40	916	18	
6GS11T	10	1,1	1,5	61						52	49	44	41	34	23				-	3	-	887	16,5	
6GS15M	14	1,5	2	85						72	69	62	58	48	32				10,5	-	50	1106	21	
6GS15T	14	1,5	2	85						72	69	62	58	48	32				-	4	-	1078	19,5	
6GS22M	21	2,2	3	128						108	104	93	87	71	48				15,9	-	70	1428	28	
6GS22T	21	2,2	3	128						108	104	93	87	71	48				-	5,9	-	1323	23	
6GS30T	29	3	4	177						150	143	128	120	99	67				-	7,8	-	1630	31	
6GS40T	38	4	5,5	232						196	188	168	157	129	87				-	10	-	2223	37	
6GS55T	52	5,5	7,5	317						268	257	230	215	177	120				-	13,7	-	2657	46	

Performances in compliance with ISO 9906 - Annex A
 Diameter of pump delivery port: 1GSL - 2GS - 4GS - 6GS: 1 1/2".

8GS, 12GS, 16GS SERIES

HYDRAULIC PERFORMANCE TABLE AT 2850 rpm, 50 Hz

PUMP TYPE	NUMBER OF STAGES	KW	HP	Q = DELIVERY																RATED CURRENT		CAPACITOR	ELECTRIC PUMP LENGTH	ELECTRIC PUMP WEIGHT
				H = TOTAL HEAD METERS COLUMN OF WATER																SINGLE-PHASE 220 V	THREE-PHASE 380-415 V			
				l/min	0	60	80	100	120	140	160	200	250	300	367	mm	kg							
					0	3,6	4,8	6	7,2	8,4	9,6	12	15	18	22			450 V						
					m ³ /h																			
8GS07M	4	0,75	1	26	24	23	22	20	18	16								5,7	-	30	703	15		
8GS07T	4	0,75	1	26	24	23	22	20	18	16								-	2,1	-	681	13,5		
8GS11M	6	1,1	1,5	39	36	34	33	31	28	24								8,2	-	40	794	16,5		
8GS11T	6	1,1	1,5	39	36	34	33	31	28	24								-	3	-	765	15,5		
8GS15M	8	1,5	2	52	48	46	44	41	37	32								10,5	-	50	884	18,5		
8GS15T	8	1,5	2	52	48	46	44	41	37	32								-	4	-	856	17		
8GS22M	13	2,2	3	84	77	74	71	67	60	51								15,9	-	70	1144	25		
8GS22T	13	2,2	3	84	77	74	71	67	60	51								-	5,9	-	1039	20		
8GS30T	17	3	4	110	101	97	93	87	78	67								-	7,8	-	1268	28		
8GS40T	23	4	5,5	149	137	132	126	118	106	91								-	10	-	1768	33		
8GS55T	32	5,5	7,5	207	191	183	175	164	147	127								-	13,7	-	2039	40		
8GS75T	43	7,5	10	279	256	246	235	220	198	170								-	19,8	-	2430	47		
12GS15M	7	1,5	2	43						37	35	33	30	25	17			10,5	-	50	1000	19,5		
12GS15T	7	1																						