



Ratio **1:1**  
Capacity **23 l/min**



Art. 33060

Art. 33061



Art. 33094

Art. 33096

**Air-operated transfer pumps 23 l/min** suitable for transferring **low-viscosity** (density) liquids such as oil, depleted oil, antifreeze liquid and allied products, **at short and medium distances**.

**They are equipped with special Teflon seals.**

**Art. 33060 Transfer pump 23 l/min** Ratio 1:1 for wall mounting (or fixed) **see page 66**

N° 1 packing  $m^3$  0,006 kg 4,3

**Art. 33061 Extensible pump 23 l/min** Ratio 1:1 complete with foot valve with filter **KR3308** applicable to the personalized suction tube. **see page 66**

N° 1 packing  $m^3$  0,006 kg 5

**Art. 33094 Transfer pump 23 l/min** Ratio 1:1 for 180/220 kg trade drums

N° 1 packing  $m^3$  0,020 kg 6,3

**Art. 33096 Transfer pump 23 l/min** Ratio 1:1 for 180/220 kg trade drums with pump bung adaptor (art. 38042)

N° 1 packing  $m^3$  0,020 kg 6,4

We recommend applying delivery hoses of min. 1/2", optimal 3/4".

N.B. The eventual application of a meter art.37701-37702-37711-37722 reduces the pump capacity to 13/15 litres max.

These pumps can only be coupled with meter 33701.

**WARNING:** Do not use flammable or corrosive liquids.

Article	33060	33061	33094 33096	33160	33161	33194 33196
Compression ratio	1:1	1:1	1:1	1:1	1:1	1:1
Air inlet connection	F 1/4" G.	F 1/4" G.	F 1/4" G.	F 1/4" G.	F 1/4" G.	F 1/4" G.
Oil outlet connection	F 1/2" G.	F 1/2" G.	F 1/2" G.	F 3/4" G.	F 3/4" G.	F 3/4" G.
Working pressure	6 - 8 bar	6 - 8 bar	6 - 8 bar	6 - 8 bar	6 - 8 bar	6 - 8 bar
Max. pressure	8 bar	8 bar	8 bar	8 bar	8 bar	8 bar
Air consumption	230 lt/min	230 lt/min	230 lt/min	270 lt/min	270 lt/min	270 lt/min
Relative capacity (free delivery at 6 bar)	23 lt/min	23 lt/min	23 lt/min	40 lt/min	40 lt/min	40 lt/min
Noise level	81 dB	81 dB	81 dB	81 dB	81 dB	81 dB
Temperature oil delivered	-10 +50°C	-10 +50°C	-10 +50°C	-10 +50°C	-10 +50°C	-10 +50°C
Max. viscosity oil delivered	80 SAE	80 SAE	80 SAE	130 SAE	130 SAE	130 SAE
Suitable for drums of	/	/	180 - 220 kg	/	/	180 - 220 kg
Weight	4 kg	4,5 kg	6 kg	5 kg	5,5 kg	6,5 kg
Suction tube length	/	/	940 mm	/	/	940 mm
Suction tube diameter	wall-mounted	/	42 mm	wall-mounted	/	42 mm