

DISINCROSTATORI PF/T DESCALING SYSTEMS TYPE PF/T

PF/T30

- Motore -Driven 450 Watt, 220V/1/50 Hz - 48V/1/50Hz
- Serbatoio -Tank PE/PVC - Volume 30 litres - kg 6
- Pompa -Pump Polypropylene/PTFE/FPM
- Portata -Delivery Q = 2 mc/h max
- Prevalenza-Head H = 22 m w.c. max

PF/T50

- Motore -Driven kW 0,25 Volt 380/3/50 Hz
- Serbatoio -Tank PE - Volume 50 lt.
- Pompa -Pump AS20 Polypropylene
- Portata -Delivery Q = 4 mc/h max
- Prevalenza-Head H = 6 m c.a. max

PF/T100

- Motore- Driven kW 1,1 - Volt 380/3/50 Hz
- Serbatoio - Tank PE - Volume 100 lt.
- Pompa - Pump AS30 Polypropylene
- Prevalenza - Head H = 12 m c.a. max

PF/T200

- Motore - Driven kW 1,5 - Volt 380/3/50 Hz
- Serbatoio - Tank PE - Volume lt. 200
- Pompa - Pump AS40 in Polypropylene
- Portata - Delivery Q = 15 mc/h max
- Prevalenza - Head H = 16 m c.a. max

PF/T220

- Motore - Driven kW 3 - Volt 380/3/50 Hz
- Serbatoio - Tank PE - Volume lt. 200
- Pompa - Pump AS50 in Polypropylene
- Portata - Delivery -Débit Q = 30 mc/h max
- Prevalenza - Head - Hauteur H = 22 m c.a. max